



PowerG D/W Contact w/ Aux Input

PGx945



Visible Link Quality Indicator

Built-in LED indicator helps installers find the optimal mounting location without needing to check the keypad.



Fully Supervised

Ensures the device is always connected and functioning properly, enhancing overall reliability.



Configurable Aux Input

Normally Open, Normally Closed, or Single End-of-Line configuration.



Long Battery Life

Powered by a 3V CR123A lithium battery for up to 8 years of battery life.



PowerG Technology

Delivers secure, long-range, and reliable performance—even in challenging environments.



Easy Configuration

All settings are managed through the system keypad for a streamlined setup and installation.



PowerG

DSC



SPECIFICATIONS

Dimensions (LxWxD)	81 x 34 x 25 mm (3.19 x 1.25 x 1 in)
Battery Life	Up to 8 years (with typical usage)
Battery Type	3V CR123A Lithium Battery (GP, Panasonic and Duracell only)
Weight (including battery)	53 g (1.9 oz)
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Relative Humidity	up to max, 93 % RH, non-condensing
Approvals & Certifications	FCC/IC UL/ULC CSFM for residential fire applications
Part Number(s)	PG9945 - 912-919 MHz PG8945 - 868 MHz PG4945 - 433 MHz



PowerG

DSC

